

NO
SWEAT®

LONG STYLE



Our NO SWEAT line is recommended for most one and two wire braided, fiber braided and wire reinforced hoses, such as: OS&D, barge and dock loading and unloading, frac hose, chemical hose etc.



The NO SWEAT LONG STYLE enjoys all the features and benefits of our NO SWEAT engineering and design. Integral one piece, ease of insertion, proprietary serration profile for increased rubber flow and retention.



Upgrade to the NO SWEAT LONG STYLE whenever your application requires higher working pressures or more retention due to increased force factors such as torsion, end pull, etc.



SIZE/STYLE	PART #	HOSE O.D. RANGE	MAX WP PSI
3"MALE PIPE	MPL300-BNS	3-34/64" to 3-52/64"	1000
4"MALE PIPE	MPL400-BNS	4-42/64" to 4-60/64"	850
6"MALE PIPE	MPL600-AANS	6-41/64" to 7-7/64"	700
6"MALE PIPE	MPL600-BNS	6-57/64" to 7-20/64"	700
3"WELD PREP	MWL300-BNS	3-34/64" to 3-52/64"	1000
4"WELD PREP	MWL400-BNS	4-42/64" to 4-60/64"	850
6"WELD PREP	MWL600-AANS	6-41/64" to 7-7/64"	700
6"WELD PREP	MWL600-BNS	6-57/64" to 7-20/64"	700



WWW.MARIOMFG.COM

Phone 337.534.4215 | Fax 337.534.4216 | 843 STEWART STREET, LAFAYETTE LA 70501

ROUGHNECK



For use in high pressure, heavy duty oil field applications. The best coupling on the market for use with various jetting, mud, vibrator, injection and frac hoses. Experience the ease of assembly and increased retention and safety with our one piece design. Also available in stainless steel.



SIZE/STYLE	PART #	HOSE O.D. RANGE	MAX WP PSI
3"HEAVY DUTY MALE PIPE	MPC300HD4500	3-55/64" to 4-28/64"	3000
4"HEAVY DUTY MALE PIPE	MPC400HD5500	5-8/64" to 5-28/64"	1000
6"HEAVY DUTY MALE PIPE	MPC600HD8000	7-32/64" to 7-60/64"	1000
3"HEAVY DUTY WELD PREP	MWC300HD4500	3-55/64" to 4-28/64"	3000
4"HEAVY DUTY WELD PREP	MWC400HD5500	5-8/64" to 5-28/64"	1000
6"HEAVY DUTY WELD PREP	MWC600HD8000	7-32/64" to 7-60/64"	1000



WWW.MARIOMFG.COM

Phone 337.534.4215 | Fax 337.534.4216 | 843 STEWART STREET, LAFAYETTE LA 70501